

# TD-500 橫式自動包裝機

## Horizontal Auto Wrapping Machine

### 機械特點 / Feature

此機型適用於包裝大型固態物品，高速運轉不影響包裝外觀，適合包裝物量產之廠家。

This auto-wrapping machine is suitable for large size of solid products. This machine features consistent heat sealing even on high speed rates. It can be modified to suit special products upon the customers' request.

### 適用包裝物 / Application

各種大型固體產品，例如米粉、面紙或餐巾紙產品。

Ideal for products such as Rice Noodles, Tissue Paper or Napkin etc.



### 規格表 / Specification

機身 / Machine	
總長 Length(cm)	476
總寬 Width(cm)	110
總高 Height(cm)	192
淨重 Net Weight(N.W.Kg)	900
毛重 Gross Weight(G.W.Kg)	1200
電源 / Electric	
電壓 Voltage(V)	220
主馬達 (HP) Main Motor(HP)	1(DC)
馬達 Motor	伺服馬達 1HP(AC) Servo Motor 1HP (AC)
電熱 Electric Heater(KW)	2.44KW 220V
控制方式 Control System	光電開關配合內藏式速度控制鈕 Electrical Switch With The Hided Speed Control Button
頻率 Frequency(HZ)	60
安全裝置 Safety Device	安全網開啟自動斷電及緊急按鈕 Emergency Stop Button

包裝型式 / Package	
封口方式 Sealing Mode	連續式熱熔封切包裝 Continuous Sealing With Heated Crimp Wheel And Straight Bar End Seal
封口構造 Sealing Structure	可調式製袋器與迴轉式熱熔封切刀 Adjustable Rotating End Seal Bars
封口型式 Sealing Style	製袋器牽引膠帶與熱熔方式封袋 Former, Controls Film & Heat Melt
進料方式 Feeding Method	進料輸送袋 Feeding Conveyor With Pusher
出料方式 Discharge Method	出料輸送袋 Discharge With Conveyor Belt
封口數目 Sealing Sides	三面封口 Seal By Three Sides
包裝速度 Packing Speed (Bags/min)	25-150(視包裝物與材料而定) 25-150 ppm, Depending On Packing Size & Material
最大包裝材料寬度 (mm) Max. Width of Packing Material	700
最大包裝物尺寸 (mm) Max. Packing Size	350×250×120 (L×W×H)
最小包裝物尺寸 (mm) Min. Packing Size	100×70×10 (L×W×H)