

# TD-400 橫式自動包裝機

## Horizontal Auto Wrapping Machine

### 機械特點 / Feature

此機種最適用於包裝物呈產之廠家，包裝速度快，高速運轉不影響包裝外觀，亦能多元化包裝。

This auto-wrapping machine is suitable for companies that require a high speed production. This machine features consistent heat sealing even on high speed rates. Suitable for a wide range of solid products. It can be modified to suit special products upon the customers' request.

### 適用包裝物 / Application

各種固體產品，如麵包，速食麵、熱狗、薑餅等食品類、餐紙巾封口、口罩等五金類。

Ideal for products such as Bread, Instant Noodles, Hot Dog, Cake, Napkin and Surgical Mask.



### 規格表 / Specification

機身 / Machine	
總長 Length(cm)	380
總寬 Width(cm)	100
總高 Height(cm)	161
淨重 Net Weight(N.W.Kg)	900
毛重 Gross Weight(G.W.Kg)	1200
電源 / Electric	
電壓 Voltage(V)	220
馬力 Main Motor(HP)	1(DC)
電熱 Electric Heater(KW)	2.4KW 220V
控制方式 Control System	光電開關配合內藏式速度控制鈕 Electrical Switch With The Hided Speed Control Button
頻率 Frequency(HZ)	60
安全裝置 Safety Device	安全網開啟自動斷電及緊急按鈕 Emergency Stop Button

包裝型式 / Package	
封口方式 Sealing Mode	連續式熱熔封切包裝 Continuous Sealing With Heated Crimp Wheel And Straight Bar End Seal
封口構造 Sealing Structure	可調式製袋器與迴轉式熱熔封切刀 Adjustable Rotating End Seal Bars
封口型式 Sealing Style	製袋器牽引膠帶與熱熔方式封袋 Former, Controls Film & Heat Melt
進料方式 Feeding Method	進料輸送袋 Feeding Conveyor With Pusher
出料方式 Discharge Method	出料輸送袋 Discharge With Conveyor Belt
封口數目 Sealing Sides	三面封口 Seal By Three Sides
包裝速度 Packing Speed (Bags/min)	25-200(視包裝物與材料而定) 25-200 ppm, Depending On Packing Size & Material
最大包裝材料寬度 (mm) Max. Width of Packing Material	500
最大包裝物尺寸 (mm) Max. Packing Size	320×200×80 (L×W×H)
最小包裝物尺寸 (mm) Min. Packing Size	120×45×9 (L×W×H)