

TD-200 小型自動包裝機 Small Auto-Packer

機械特點 / Feature

此機型結構設計精密，體積小、不佔空間，適用於門市店面。包裝尺寸可靈活調整，適合少量多樣之產品包裝需求。
Compact machine structure and suitable for retail store. Easy to operate, packing size can be modified at customers' request. Suitable for small-volume and large-variety production.

適用包裝物 / Application

此機適用於小型固體物包裝，如鳳梨酥、牛軋糖、巧克力、小點心等食品類；五金類等材料包裝亦適用於本機型。
Ideal for smaller sized articles and solids such as Pineapple cake, Nougat, Chocolates and Cookies. This machine is also suitable for Hardware packing.



規格表 / Specification

機身 / Machine		包裝型式 / Package	
總長 Length(cm)	230	封口方式 Sealing Mode	連續式熱熔封切包裝 Continuous Sealing With Heated Crimp Wheel And Straight Bar End Seal
總寬 Width(cm)	72	封口構造 Sealing Structure	可調式製袋器與迴轉式熱熔封切刀 Adjustable Rotating End Seal Bars
總高 Height(cm)	140	封口型式 Sealing Style	製袋器牽引膠帶與熱熔方式封袋 Former, Controls Film & Heat Melt
淨重 Net Weight(N.W.Kg)	475	進料方式 Feeding Method	進料輸送袋 Feeding Conveyor With Pusher
毛重 Gross Weight(G.W.Kg)	625	出料方式 Discharge Method	出料輸送袋 Discharge With Conveyor Belt
電源 / Electric		封口數目 Sealing Sides	三面封口 Seal By Three Sides
電壓 Voltage(V)	220	包裝速度 Packing Speed (Bags/Min)	25-150(視包裝物與材料而定) 25-150 ppm, Depending On Packing Size & Material
馬力 Main Motor(HP)	1(DC)	最大包裝材料寬度 (mm) Max. Width Of Packing Material	300
電熱 Electric Heater(KW)	2.4KW 220V	最大包裝物尺寸 (mm) Max. Packing Size	150×100×40 (L×W×H)
控制方式 Control System	彩色人機，配合 PLC 控制 Colorful HMI Controlled By PLC	最小包裝物尺寸 (mm) Min. Packing Size	40×15×3 (L×W×H)
頻率 Frequency(HZ)	60		
安全裝置 Safety Device	安全網開啟自動斷電及緊急按鈕 Emergency Stop Button		